

# PURO-CT

## Oil/water separator

### PRODUCT FEATURES

The PURO-CT range of oil/water separators separates oil from condensate, generated by compressed air systems.

The PURO-CT achieves efficient separation of oil from condensate by means of directing the condensate through various separation stages. As condensate flows in to the PURO-CT, the oil is filtered out through various filtration elements.

The PURO-CT uses adsorption filter materials, instead of a weir, to remove the bulk of the oil.

The life of the PURO-CT first stage filtration element is determined by the amount of oil removed, not by the amount of condensate treated.

The PURO-CT carbon element is utilised only for final purification purposes and ensures that the targeted values of <10 ppm are achieved.

The professional design of the PURO-CT is incredibly compact and the elements are lightweight, maximising the ergonomic factors when carrying out routine maintenance.

Brass connection inserts ensure a secure fixing of the condensate inlets and outlet connections.



### COMMERCIAL BENEFITS

- Operates with all JORC type condensate drains (both timer controlled and level sensed)
- Three models covering up to 15 m<sup>3</sup>/m in compressor capacity offering sizing flexibility
- Private labelling is possible including different coloured lids
- Freight cost advantages, even the largest model can be sent as a parcel shipment

### TECHNICAL ADVANTAGES

- Small foot print
- Light and easy replacement of elements
- Simple installation and maintenance procedures
- Sample bottle and test drain for output testing/measuring the ppm value (indication)
- Overflow safety indicator.
- All JORC type drains can be used in combination with the PURO-CT

# PURO-CT

## Oil/water separator

### TECHNICAL SPECIFICATIONS

Model	CT 3 (3 m <sup>3</sup> /min.)	CT 7 (7 m <sup>3</sup> /min.)	CT 15 (15 m <sup>3</sup> /min.)
Target oil output value	<10 ppm	<10 ppm	<10 ppm
Max. oil adsorption (litres)	3	7	15
Inlet connections (brass) outlet connections (brass)	1/2" (1) 1/2"	1/2" (1) 1/2"	1/2" (2) 1/2"
TEST valve (brass)	Yes	Yes	Yes
Overflow indicator	Yes	Yes	Yes
Housing material	PPC	PPC	PPC
Total recyclable	Yes	Yes	Yes
Housing colour	Grey	Grey	Grey
Standard lid colour	Black	Black	Black

### SEPARATION OF:

Mineral lubricants	Yes
Synthetic lubricants	Yes
Stabile condensate emulsions*	Yes
Polyglycol*	Yes

*\*Special elements required, please consult factory*

### ADDITIONAL FEATURES

All PURO-CT models can accept condensate discharge from efficient intelligent drains, cost effective timer drains, float drains and manual drains.

**Consult JORC for:**

- \* Larger compressor capacities
- \* Special element solutions
- \* Element selection condensate test kit
- \* Private labelling

### JORC is NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, JORC reserves the right to revise information without notice and without incurring any obligation

**JORC Industrial BV**      Tel: +31 45 5242427  
 Pretoriastraat 28  
 NL-6413 NN Heerlen      info@jorc.nl  
 The Netherlands      www.jorc.eu